

# Dräger Verticus 5



Dräger high pressure breath air compressor for the effort there, where large delivery volume is required and the noise level is secondarily.



Verticus 5  
with filling hoses



Verticus 5  
direct-inflation valves

Dräger Verticus 5 supplies breathing air quality in accordance with DIN EN 12021.

The casing of the plant is modular developed. Additionally the removable side doors make a comfortable entrance possible for all necessary maintenance work. The sound pressure level amounts to  $72 \pm 2\text{dB(A)}$  in 1m distance in accordance with DIN 45635.

The compressor B-control contains a language selection.

Additionally the Dräger Verticus 5 has safety system, the P61/P81 - filter system with SECURUS, a condensate drain mechanism and a condensate collecting system with 10 l-cans (optionally 40 l-cask) with optical level announcement.

The three-phase motor is operated with 220V to 380V and 400V to 690V with a frequency of 50/60Hz. The capacity amounts to approx. 5,5 to 15kW.

Options:

- distribution switchboard PN 220/330 bar
- without filling mechanism
- with filter system P81

## TECHNICAL DATA

	Type	Delivery L/min	Speed U/min	Motor kW	Filter system	Weight approx. kg	Dimensions [L x W x H] cm
225 - 330 bar	V 260	260	1.185	5,5	P61	395	148 x 83 x 152
	V 320	320	1.470	7,5	P61	400	148 x 83 x 152
	V 500	540	1.230	11,0	P61	440	148 x 83 x 152
	V 600	680	1.400	15,0	P61	455	148 x 83 x 152
420 bar	V 260 - 420	260	1.185	5,5	P61	395	148 x 83 x 152
	V 320 - 420	320	1.470	7,5	P61	450	148 x 83 x 152
	V 500 - 420	520	1.140	11,0	P61	455	148 x 83 x 152
	V 600 - 420	600	1.320	15,0	P61	465	148 x 83 x 152

## ORDER LIST

V 260 - PN 225 bar	65 26 600
V 260 - PN 330 bar	65 26 601
V 260 - PN 225/330 bar	65 26 602
V 260 - PN 330 bar – without filling mechanism	65 26 603
V 260 - 420 / PN 420 bar - without filling mechanism	65 26 617
V 320 - PN 225 bar	65 26 604
V 320 - PN 330 bar	65 26 605
V 320 - PN 225/330 bar	65 26 606
V 320 - PN 330 bar - without filling mechanism	65 26 607
V 320 - 420 / PN 420 bar - without filling mechanism	65 26 619
V 500 - PN 225 bar	65 26 608
V 500 - PN 330 bar	65 26 609
V 500 - PN 225/330 bar	65 26 610
V 500 - PN 330 bar - without filling mechanism	65 26 611
V 500 - 420 / PN 420 bar - without filling mechanism	65 26 637
V 600 - PN 225 bar	65 26 612
V 600 - PN 330 bar	65 26 613
V 600 - PN 225/330 bar	65 26 613
V 600 - PN 330 bar - without filling mechanism	65 26 614
V 600 - 420 / PN 420 bar - without filling mechanism	65 26 639



### SUBSIDIARIES

**AUSTRALIA**  
 Draeger Safety Pacific Pty. Ltd.  
 Notting Hill Vic 3168  
 Tel +61 3 92 65 50 00  
 Fax +61 3 92 65 50 95

**FRANCE**  
 Draeger Industrie S.A.  
 67025 Strasbourg Cedex  
 Tel +33 388 40 76 76  
 Fax +33 388 40 76 67

**SINGAPORE**  
 Draeger Safety Asia Pte. Ltd.  
 139950 Singapore  
 Tel +65 68 72 92 88  
 Fax +65 67 73 20 33

**UNITED KINGDOM**  
 Draeger Safety UK Ltd.  
 Blyth, Northumberland NE24 4RG  
 Tel +44 16 70 35 28 91  
 Fax +44 16 70 35 62 66

**CANADA**  
 Draeger Canada Ltd.  
 Mississauga, Ontario L5N 6P9  
 Tel +1 905 821 8988  
 Fax +1 905 821 2565

**MEXICO**  
 Draeger Safety S.A. de C.V.  
 Querétaro, Oro México  
 Tel +1 412 787 8383  
 Fax +1 412 787 2207

**REP. OF SOUTH AFRICA**  
 Draeger South Africa (Pty) Ltd.  
 Bryanston 2021  
 Tel +27 11 465 99 59  
 Fax +27 11 465 69 53

**USA**  
 Draeger Safety, Inc.  
 Pittsburgh, PA 15275  
 Tel +1 412 787 8383  
 Fax +1 412 787 2207

**P.R. CHINA**  
 Beijing Fortune Draeger  
 Safety Equipment Co., Ltd.  
 Beijing 101300  
 Tel +86 10 80 49 80 00  
 Fax +86 10 80 49 80 05

**NETHERLANDS**  
 Draeger Safety Nederland B.V.  
 2700 AH Zoetermeer  
 Tel +31 79 344 46 66  
 Fax +31 79 331 62 26

**SPAIN**  
 Draeger Safety Hispania S.A.  
 28034 Madrid  
 Tel +34 91 358 02 44  
 Fax +34 91 729 48 99

**Draeger Safety AG & Co. KGaA**  
 Revalstrasse 1  
 23560 Luebeck, Germany  
 Tel +49 451 882 0  
 Fax +49 451 882 2080  
 www.draeger-safety.com