

Infinity® Vista XL Patient Monitor

Bedside or transport monitor designed to support adult, pediatric and neonatal patients with various acuity levels. Mount the Vista XL to the wall or to a roll-stand or hand carry. The monitor automatically stores events that occur while on transport and prints them upon connection to a recorder.



FEATURES

- Works as a standalone device or connects to Infinity Network via DirectNet or wireless adapter for seamless wired to wireless networking
- Scales using software options
- Provides laser printer reports and strip chart recordings

Monitoring Capabilities

Neonatal, pediatric and adult applications

TECHNICAL DATA

SUPPORTED PARAMETERS

ECG

Displays up to 12 leads	
Available leads	I, II, III, aVR, aVF, aVL, V, V+, [V, aVR aVF, aVL only with 5- and 6-lead sets, V+ only with 6-lead set, TruST® 12-lead with reduced lead-set (6-wire): I, II, III, aVL, aVR, aVF, dV1, V2, dV3, dV4, V5 and dV6 (indicated for adults and pediatrics). ¹
Measuring range (heart rate)	15 to 300 bpm
Accuracy	± 2 bpm or ± 1% (whichever is greater)
Frequency ranges	Filter off: 0.05 to 40 Hz display; 0.05 to 125 Hz printer Monitoring filter: 0.5 to 40 Hz; ESU filter: 0.5 to 16 Hz



Infinity Vista XL
Supports mid- and high-acuity patients in any care unit.

¹ Optimum performance of TruST leads is based on a minimum 0.3mV amplitude and QRS duration <180 milliseconds on patients with a body surface area (BSA) of 1.5 – 2.5 m². TruST 12-lead reduced lead-set ECG algorithm provides 12-lead monitoring using a standard 6-wire lead-set and standard lead placement for limb leads, V2 and V5. ARIES software option enhances TruST 12-lead monitoring with the addition of 12-lead ST Analysis.

CONTINUING TECHNICAL DATA**QRS Detection Range**

Amplitude	0.5 to 5 mV
Duration	Adult and pediatric: 70 to 120 msec Neonatal: 40 to 120 msec
Alarms	User-selectable upper and lower limits
Pacer detection (adult/pediatric)	Leads: I, II or III Amplitude: ± 2 to ± 700 mV Width (d.): 0.2 to 2.0 msec
Accessories	With 3-lead ST option: Choice of any 3 available leads With ARIES option: Up to 12 leads

ST (not intended for neonates)

Available leads	Up to 12 leads (choice of any 3 available leads)
ST complex length	892 msec (-300 to +600 msec from fiducial point)
Sample rate	225 samples/sec
Frequency response	0.05 – 40 Hz

Isoelectric measurement point

Measuring range	Start of ECG complex to fiducial point
Default	QRS onset – 28 msec

ST measurement point

Adjustment range	Fiducial point to end of ECG complex
Point default	QRS offset +80 msec
Update interval	15 sec, 1 normal beat required
Resolution	± 0.1 mm
Trends	Graphical, tabular and graphical mini-trends
INOP Alarm	Yes
Upper and lower ST alarms	± 15 mm, ± 0.1 mm increments
Duration of ST event to trigger alarm	None, 15, 30, 45, 60 seconds

Arrhythmia Detection

Adult and Pediatric	Yes
Neonatal	No, Bradycardia is available as a low heart rate alarm for neonates.
ARR Mode	User Selectable; OFF, Basic or Advanced
Basic ARR (standard)	Asystole, ventricular fibrillation, ventricular tachycardia and artifact (ARR label displayed to register arrhythmia occurrence)
Advanced ARR (option)	Ventricular run, accelerated idioventricular rhythm, supra-ventricular tachycardia, couplet, bigeminy, tachycardia, bradycardia, pause and also supports PVC/min parameter output.

Respiration

Sensing leads	I, II (user-selectable)
Measuring method	Impedance pneumography
Auxiliary current	$\leq 10\mu\text{A}$ for any active electrode
Detection threshold	0.15 Ω to 4.0 Ω in manual mode (user adjustment) 0.2 Ω to 1.5 Ω in auto mode (automatic adjustment)
Measuring range	0 to 155 breaths per min
Accuracy	± 1 breath/min or 2% of rate (whichever is greater)
Apnea detection	For neonatal and pediatric patients
Alarms	User-selectable upper and lower respiration rate

Pulse Oximetry (SpO₂)

SpO ₂ algorithm	Masimo® SET® (Signal Extration Technology) Masimo provides the industry gold standard for motion tolerant pulse oximetry. See additional product datasheet for more detailed specifications.
SpO ₂ algorithm	Nellcor™ OxiMax™ 2 See additional product datasheet for more detailed specifications.
SpO ₂ algorithm	Dräger's OxiSure® SpO ₂
Dräger's OxiSure® SpO₂	
Connection	MultiMed® pods (SpO ₂ port)
Displayed parameters	Saturation (fraction of oxyhemoglobin to functional hemoglobin) and pulse (rate and waveform)
Measuring method	Transmission spectrophotometry
Measuring range	SpO ₂ : 1 to 100% Pulse: 30 to 250 bpm
Accuracy	SpO ₂ : 0 to 69% not specified SpO ₂ : 70 to 100%: ± 2% (± 3% for neonates; Masimo® LNOP-Ear: ± 3.5%; Nellcor® DS100A: ± 3%) Pulse: ± 3 bpm or ± 3% (whichever is greater)
Alarms	User-selectable upper and lower limits for SpO ₂ and pulse rate Life-threatening desaturation alarm in neonatal mode only
Accessories	Dräger Medical-approved Masimo or Nellcor sensors Dräger Medical reusable SpO ₂ sensors (not intended for neonates).

Temperature

Displayed parameters	Absolute and delta temperatures
Measuring range	Absolute: -5° C to 50° C Delta: 0° C to 55° C
Resolution	0.1° C
Accuracy	Absolute: ± 0.1° C Delta: ± 0.2° C
Alarms	User-selectable upper and lower limits for absolute and delta values
Accessories	Dräger Medical-approved core and skin probes

Noninvasive Blood Pressure (NBP)

Displayed parameters	Systolic, Mean and Diastolic pressures
Measuring method	Oscillometric utilizing step deflation
Modes of operation	Manual (single measurement); Continuous (5 minutes) and Interval
Interval times	1, 2, 2.5, 3, 5, 10, 15, 20, 25, 30, 45, 60, 120 and 240 minutes
Heart rate measuring range	30 to 240 bpm

Pressure measuring range

Adult	Systolic: 30 to 250 mmHg Mean: 20 to 230 mmHg Diastolic: 10 to 210 mmHg
Pediatric	Systolic: 30 to 170 mmHg Mean: 20 to 150 mmHg Diastolic: 10 to 130 mmHg
Neonatal	Systolic: 30 to 130 mmHg Mean: 20 to 110 mmHg Diastolic: 10 to 100 mmHg

CONTINUING TECHNICAL DATA**Cuff pressure**

Default inflation pressure	
Adult	160 mmHg \pm 10 mmHg
Pediatric	120 mmHg \pm 10 mmHg
Neonatal	110 mmHg \pm 10 mmHg
Inflation pressure after a valid measurement	
Adult	(Last Systolic +25 mmHg) \pm 10 mmHg
Pediatric	(Last Systolic +25 mmHg) \pm 10 mmHg
Neonatal	(Last Systolic +30 mmHg) \pm 5 mmHg
Maximum inflation pressure	
Adult	265 mmHg \pm 5 mmHg
Pediatric	180 mmHg \pm 10 mmHg
Neonatal	142 mmHg \pm 10 mmHg
Minimum inflation pressure	
Adult	110 mmHg \pm 10 mmHg
Pediatric	90 mmHg \pm 10 mmHg
Neonatal	70 mmHg \pm 10 mmHg
Connector	Quick-release connector with single airway

Invasive Blood Pressure

Displays up to 8 pressures	
Measuring method	Resistive strain gauge transducer
Display resolution	1 mmHg
Measuring range	-50 to 400 mmHg (after zeroing)
Frequency ranges	DC to 8 Hz, DC to 16 Hz, or DC to 32 Hz (user-selectable)
Zero balance range	\pm 200 mmHg
Transducer specifications	Dräger Medical-approved transducers with a resistance of 200 to 3000 Ω and an equivalent pressure sensitivity of 5 μ V/V/mmHg \pm 10%
Accuracy	\pm 1 mmHg or \pm 3%, exclusive of transducer (whichever is greater)
IBP alarms	User-selectable upper and lower limits for systolic, mean and diastolic pressures
Accessories	Dräger Medical-approved pressure transducers

Cardiac Output

Parameter display	Cardiac output, Blood Temperature, Injectate Temperature
Measuring method	Thermodilution
Connection	HemoMed™ pod

Measuring range

Cardiac output	0.5 to 20 L/min
Blood temperature	25° C to 43° C (77° F to 109° F)
Injectate temperature	-5° C to +30° C (23° F to 86° F)

Accuracy

Cardiac output	\pm 5% (with 0° C injectate)
Injectate temperature	\pm 0.25° C
Degree of protection against electric shock	Type CF
Defibrillation protection	Defibrillation-Proof Applied Part per IEC 60601-1

DISPLAY SPECIFICATIONS

Type	Thin Film Transistor-Liquid Crystal Display Active Matrix (TFT-LCD)
Size (Delta)	264 mm (10.4 in.) diagonal
Channels	5 standard, 6, 8 optional
Viewing area	211 x 158 mm (8.3 x 6.2 in.)
Resolution	640 x 480 pixels
Rotary knob	Easy-to-use menu structure and fixed keys

Alarms

Priorities	3; High (Life Threatening), Medium (Serious), Low (Advisory)
Audio alarm tones	User Selectable: Infinity, IEC 1 ² or IEC 2 ²

Connections

Multimed[®] cables, Masimo SET[®] SmartPod[®], Nellcor OxiMax SmartPod², HemoMed™ Pod, NBP Input, etCO₂ module, Infinity Docking Station, analog output, QRS sync output, RS 232, remote keypad, and Scio[®] Four modules.

Analog output

Signals	ECG, arterial blood pressure
Delay	≤25 msec

Infinity Network

Networking method	DirectNet or Wireless
Wireless encryption	None, WEP, WPA2 ²

See individual product datasheets for detailed information.

Physical Specifications

Cooling	Convection
Size H x W x D	253 x 365 x 190 mm (10.0 x 14.4 x 7.5 in.)
Weight	5.8 kg (12.7 lbs.)
with external battery	6.4 kg (14.0 lbs.)

Information Management Capabilities

Data storage	24 hours of trended parameter information
Data resolution	30-second sampling
Trend tables	1-, 5-, 15-, 30- or 60-minute display formats
Trend graphs	1-, 2-, 4-, 8-, 12- or 24-hour display formats

Electrical Specifications

Input voltage	11 to 15 V DC
Power consumption	≤70 Watts (fully loaded)
Patient leakage current	≤10 μA
Protection class	Internally powered (per IEC 60601-1) and for use with specified Class 1 power supplies.
Power requirements	100 to 240 V AC, 3 A
Frequency	50 to 60 Hz
Chassis leakage current	<300 μA @ 120 V AC <500 μA @ 220 V AC

CONTINUING TECHNICAL DATA

BATTERY SPECIFICATIONS

Internal battery	Battery type: lithium-ion Battery capacity: 180 minutes
Charging time	6.5 hours at 25° C
External auxiliary battery	Battery type: sealed lead-acid Battery capacity: 50 minutes Charging time: 3.5 hours at 25° C
Size (external auxiliary battery)	62 x 182 x 24 mm
H X W X D	(2.4 x 7.2 x .9 in.)
Weight	0.635 kg (1.4 lbs.)

Battery capacity varies with parameter configuration. The battery capacity specified above is under the following load conditions: MultiMed with SpO₂ sensor, 2 temperature probes, HemoMed pod with 4 IBP transducers and a catheter, NBP taking measurements every 15 minutes, LCD Transport Brightness at 50%, and no continuous tone being generated.

Battery capacity may diminish after extended use.

Environmental Requirements

Temperature range

Operating	10° C to 40° C (50° F to 104° F)
Storage	-20° C to 40° C (-4° F to 104° F)

Relative humidity

Operating	20% to 90%, non-condensing
Storage	10% to 95% (with packaging)


Atmospheric pressure

Operating	525 to 795 mmHg (70 to 106 kPa)
Storage	375 to 795 mmHg (50 to 106 kPa)

Standards

IEC 60601-1(2nd edition) and applicable particular and collateral standards,
IEC 60601-1-2:2007, Electromagnetic compatibility CISPR 11, Class B

The Vista XL monitor complies with Medical Devices Directive
(MDD) 93/42 EEC and bear the CE mark.



MT-1126-2007

MultiMed Pod



MT-2185-2003

HemoMed Pod



MT-9016-2006

Recorder

ORDERING INFORMATION

Vista XL Monitor	MS18986
------------------	---------

Note: Monitor power supply, MultiMed, and all patient connection and intermediate cables must be ordered separately.

Power Cables

Europe, CEE 7, 2.5 m	4321712
North America, 5-15R, 2.25 m	4321720
Switzerland, SEV 1 01 1, 2.25 m	4321613
Great Britain, BS 1363, 3 m	1851713
Australia, New Zealand, AS3112, 3 m	1851705
China, AS 3112, 3 m	1859714
Denmark, 3 m	1851721

Mounting

Monitor Handle Hook Mount	MS15202
---------------------------	---------

MultiMed Pods and Cables

Multi-parameter cables to monitor
3-, 5- or 6- lead ECG, impedance respiration, SpO₂* and one temperature
(two temperatures with Y-cable)

MultiMed Plus, 2.5 m	MS20093
MultiMed Plus OR, 2.5 m	MS20094
Supports integrated ESU filter for operating room environments.	
MultiMed 5, 2.5 m	3368391
MultiMed 6, 2.5 m	5191221
NeoMed, 2.5 m	5590539
3-lead ECG, impedance respiration, two temperatures, SpO ₂ * and FiO ₂ .	
MultiMed or NeoMed Pole/Rail Mount	MP00721

*SpO₂ measurements are not available from the MultiMed pods and cables if you are using an alternate source of SpO₂.

SpO₂ Pods

Masimo SET SpO ₂ SmartPod ³	MS16901
Nellcor OxiMax SpO ₂ SmartPod ^{2, 3}	MS23997

Software Options

Vista XL	
6 waveform channel option	MS15057
8 waveform channel option	MS15058
Arrhythmia II option (ACE [®])	MS15054
**Wireless option	MS15059
3-lead ST Analysis Option (not required with 12-lead option)	MS15055
12-lead ST (includes TruST and 12-lead option for non-diagnostic reports)	MS15852
OR mode option (stored in the monitor)	MS17653

**Wireless LAN PC card (MS25009²), and access point installation is required for wireless monitoring.

Optional Modules and Hardware Accessories

Invasive Blood Pressure Adapters	
2 IBP Y-adapter, 10-pin	5731281
2 IBP Y-adapter, 7-pin	5592147

CONTINUING ORDERING INFORMATION**Hemodynamic Monitoring**

HemoMed Pod ³	5588822
Provides management of up to 4 invasive blood pressures and cardiac output.	

etCO₂, Gas Monitoring

etCO ₂ module ³ (Mainstream or Sidestream)	4319310
Scio Four Modules ³	6871810
Scio Four Oxi plus, Scio Four plus, Scio Four Oxi and Scio Four modules	

Printing/Recording Options

R50 recorder ³	5952630
R50N network recorder ³	5740068
Infinity Network laser printer (115 V)	6556513
Infinity Network laser printer (220 V)	6556539

Other Accessories

Remote keypad	5203042
External battery (sealed lead acid)	5592097
External battery charging station (charges four batteries simultaneously)	5597377

² Requires VF8 software

³ Refer to individual module or pod datasheet for additional information.

Masimo and SET are registered trademarks of Masimo Corporation.

Nellcor and OxiMax are trademarks of Covidien; Covidien with logo and TM marked brands are trademarks of Covidien AG or its affiliate.

HEADQUARTERS

Drägerwerk AG & Co. KGaA
Moislinger Allee 53–55
23558 Lübeck, Germany

www.draeger.com

**REGION EUROPE CENTRAL
AND EUROPE NORTH**

Dräger Medical GmbH
Moislinger Allee 53–55
23558 Lübeck, Germany
Tel +49 451 882 0
Fax +49 451 882 2080
info@draeger.com

REGION EUROPE SOUTH

Dräger Médical S.A.S.
Parc de Haute
Technologie d'Antony 2
25, rue Georges Besse
92182 Antony Cedex, France
Tel +33 1 46 11 56 00
Fax +33 1 40 96 97 20
dlimfr-contact@draeger.com

**REGION MIDDLE EAST, AFRICA,
CENTRAL AND SOUTH AMERICA**

Dräger Medical GmbH
Branch Office Dubai
Dubai Healthcare City, P.O. Box 505108
Dubai, United Arab Emirates
Tel + 971 436 24 762
Fax + 971 436 24 761
contactuae@draeger.com

REGION ASIA / PACIFIC

Dräger Medical
South East Asia Pte Ltd
25 International Business Park
#04-27/29 German Centre
Singapore 609916, Singapore
Tel +65 6572 4388
Fax +65 6572 4399
asia.pacific@draeger.com

REGION NORTH AMERICA

Dräger Medical, Inc.
3135 Quarry Road
Telford, PA 18969-1042, USA
Tel +1 215 721 5400
Toll-free +1 800 437 2437
Fax +1 215 723 5935
info.usa@draeger.com

Manufacturer:

Dräger Medical Systems, Inc.
Telford, PA 18969, USA
The quality management system at
Dräger Medical Systems, Inc. is
certified according to ISO 13485,
ISO 9001 and Annex II.3 of Directive
93/42/EEC (Medical devices).