



Dräger VarioGard® 3200 CAT

Detector for flammable gases and vapours

The Dräger VarioGard® 3200 CAT is a digital transmitter with an integrated catalytic DrägerSensor®. It detects flammable gases such as methane, LPG and hydrogen in non Ex areas, such as underground garages and laboratories.

Benefits

Digital function

The Dräger VarioGard 3200 CAT is connected with the controller via the digital VarioGard bus. This is how it is supplied with electricity and how it transmits its measuring results. You can easily control the entire VarioGard system via the VarioGard bus.

High reliability

The Dräger VarioGard 3200 CAT is equipped with a catalytic DrägerSensor. This sensor measures the concentration of flammable gases in the ambient air. The measured values are transmitted digitally to the controller and displayed there. An alarm is triggered if the gas concentration exceeds one or more of the limit values configured.

Easy operation

Operation is extremely easy. You can make all configurations comfortably from the controller using VarioGard software. You can configure and monitor four current limit values and four averages over time for each transmitter. The alarms are optically and acoustically displayed on the transmitter and transmitted to the controller. A three-colour LED indicates the operating status of the transmitter. The calibration is controlled using a magnetic wand via contact points.

Individually configurable

The VarioGard 3200 CAT is adapted to your system. Depending on the application, three different different gas libraries are available: LPG for garages, CH₄ for methane monitoring and H₂ for laboratories that do not require explosion protection.

Focus on sustainability

The VarioGard transmitter aligns with Dräger's sustainability philosophy by incorporating durable DrägerSensors, enabling an extended service life for the device. The new housing design optimises material usage compared to its predecessor. Additionally, existing accessories and electronic spare parts from the previous series remain compatible, reducing waste. Dräger also facilitates the recycling of old devices by accepting them for disposal.

Details



D-15318-2023

Dräger VarioGard® 3200 CAT during normal operation



D-15319-2023

Dräger VarioGard® 3200 CAT during normal operation



D-15320-2023

Dräger VarioGard® 3200 CAT with gas alarm

System Components



ST-9754-2007

Dräger VarioGard® Central Unit

The Dräger VarioGard® Central Unit is at the center of a cost-efficient, modular gas detection system. A digital Bus makes it possible to connect and manage up to 100 transmitters for various gases.



D-10614-2022

Dräger VVP 1000

The Dräger VVP 1000 is a 10" touch panel that provides a clear and simple display of all data from your Dräger VarioGard® gas detector. The touch panel visualises all relevant information such as measurement values and status messages in a way that is well organised and easy to understand.

Accessories

D-2215-2015



Test gas

D-85363-2013



Magnetic wand (blue)

for menu access

D-5952-2014



Calibration adapter VarioGard

ST-5690-2006



Cable inlet M20 x 1.5 (set of 10)

Technical Data

Dräger VarioGard® 3200 CAT

Type	Transmitter for the measurement of concentrations of gases in the ambient air	
Gases and measuring ranges	LPG	0 to 100 %LEL
	Methane	0 to 100 %LEL
	Hydrogen	0 to 100 %LEL
Display	3-colour LED (green, yellow, red): Operation, Maintenance, Alarm	
Input	2 function buttons	
Alarm output	Horn and red LED	
Alarms	8 adjustable alarm thresholds	

Electrical Data

Wiring	3-wire
Communication	Dräger VarioGard® Bus
Supply voltage	16 to 30 VDC

Housing

Material	Plastic ABS light grey RAL 7035
Protection Class	IP65
Dimensions	124mm x 94mm x 63mm (W x H x D)
Weight	400 g
Cable inlet	M20 x 1,5; 6 to 12 mm

Ambient Conditions

Temperature	-20 °C to +50 °C / -4 °F to +122 °F
Humidity	10 to 95 % RH, non-condensing
Pressure	700 to 1,300 hPa / 23.6 to 32.5 inch Hg

Directives and standards

VDI 2053 (2004) Ventilation systems for garages
EN 50545-1 Measurement of toxic gases in garages and tunnels
CE marking Electric safety

Ordering Information

Dräger VarioGard® 3200 CAT

Dräger VarioGard® 3200 CAT EX	37 21 952
-------------------------------	-----------

Accessories

Magnetic Wand	45 44 101
Calibration adapter VarioGard® 3xx0/23x0	83 22 015
Cable inlet M20 x 1.5 (set of 10)	83 15 420
Software-Set VarioGard® (incl. USB Adapter)	83 22 016
Instruction for Use VarioGard®	90 33 185

Not all products, features, or services are for sale in all countries.
Mentioned Trademarks are only registered in certain countries and not necessarily in the country
in which this material is released. Go to www.draeger.com/trademarks to find the current status.

CORPORATE HEADQUARTERS

Drägerwerk AG & Co. KGaA

Moislinger Allee 53-55
23558 Lübeck, Germany
www.draeger.com

Region Europe

Dräger Safety AG & Co. KGaA

Revalstraße 1
23560 Lübeck, Germany
☎ +49 451 882 0
☎ +49 451 882-2080
✉ info@draeger.com

REGION ASIA PACIFIC

Draeger Singapore Pte. Ltd.

61 Science Park Road
The Galen #04-01
Singapore 117525
☎ +65 6872 9288
☎ +65 6259 0398
✉ asia.pacific@draeger.com

Region Central and South America

Dräger Indústria e Comércio Ltda.

Al. Pucurui - 51 - Tamboré
06460-100 Barueri, São Paulo
☎ +55 (11) 4689-4900
✉ relacionamento@draeger.com

Manufacturer

Region Middle East, Africa

Drägerwerk AG & Co. KGaA

Branch Office
P.O. Box 505108 Dubai, United Arab
Emirates
☎ +971 4 4294 600
☎ +971 4 4294 699
✉ contactuae@draeger.com



Locate your Regional Sales
Representative at:
www.draeger.com/contact