

## Dräger Interlock® XT Alcohol Screening Device with Immobilizer

The Dräger Interlock® XT is a breath-alcohol measuring instrument that can prevent a vehicle from being started if the driver's breath alcohol concentration is higher than a prescribed limit. It meets worldwide device requirements, offers the greatest possible convenience for the user, and sets a new standard for alcohol interlocks. FOR USE WITH AN IGNITION INTERLOCK RESTRICTION ONLY.



## Benefits

---

### Requests breath sample, enables ignition

Prior to starting the engine, the Dräger Interlock XT requests a breath sample. If alcohol is detected above a prescribed limit, the immobilizer system prevents the motor from starting. Otherwise, the starter is activated for the driver to start the vehicle. The device will also prompt the driver to retest periodically while en route. The device will not disrupt the engine function once the engine has been started, but the event will be recorded.

---

### High measurement accuracy

The Dräger Interlock XT determines the breath alcohol concentration via an electro-chemical sensor system. The device is responsive to alcohol only.

---

### Fast usability

To avoid long waiting periods, Dräger put emphasis on the Interlock XT being ready to use. Its functionality is as good at -40 °F or +185 °F as it is in normal conditions. The name affix "XT" stands for "eXtended Temperature".

---

### Safe from manipulation

The device immediately detects any attempt to use auxiliaries, such as air pumps or filters to bypass the Dräger Interlock XT. It will prevent the motor from starting in such cases.

---

### All events recorded in a data memory

The data memory records more than 30,000 events and can be read via special PC software.

## Accessories



### Mouthpieces

Mouthpieces are sold in packs of 5 only.

## Related Products



### Dräger Interlock™ 7000

When personnel safety and company property are at risk, the Dräger Interlock 7000 should be your first choice. The 7000, an ignition interlock device, prevents a vehicle from starting if the driver's breath alcohol concentration is higher than a preset limit. In addition, an intelligent camera, mouth alcohol detection, and GPRS options support your company's best interests.

## Technical Data

Operating Temperature	-40 to 185 °F (-40 to +85 °C)
Operating Humidity	20 to 98 % RH
Operating Atmospheric Pressure	600 to 1100 hPa
Ready for Test	No influence of changes in altitude on the measurement result <20 seconds (above 20 °C / 68 °F) <3 minutes (at -40 °C / -40 °F)
Display	Graphic LC-display in the handset with full text messages
Measurement Range	Corresponding to 0.000 % and 0.500 %
Accuracy	Exceeds NHTSA specifications
Dimensions	Handset 5.9" x 2.8" x 1.6" Control Box 4.5" x 4.1" x 1.6"
Weight	Handset 0.4 lb Control Box 0.7 lb

Not all products, features, or services are for sale in all countries.  
Mentioned Trademarks are only registered in certain countries and not necessarily in the country in which this material is released. Go to [www.draeger.com/trademarks](http://www.draeger.com/trademarks) to find the current status.

**CORPORATE HEADQUARTERS**  
Drägerwerk AG & Co. KGaA  
Moislinger Allee 53–55  
23558 Lübeck, Germany  
[www.draeger.com](http://www.draeger.com)

**USA**  
 Draeger, Inc.  
7256 S. Sam Houston Parkway W.,  
Suite 100  
Houston, TX 77085  
1 800 4DRAGER  
(1 800 437 2437)

**CANADA**  
 Draeger Safety Canada, Ltd.  
2425 Skymark Ave., Unit 1  
Mississauga, Ontario L4W 4Y6  
1 877 DRAGER1  
(1 877 372 4371)

Locate your Regional  
Sales Representative at:  
[www.draeger.com/contact](http://www.draeger.com/contact)

